


Drehmoment / Torque
 Zahnkranz / spider 95 Sh A T-PUR
 (Zahnkranz / spider 95 Sh A)
 $T_{KN} = 12800 \text{ Nm}$
 $T_{Kmax} = 25600 \text{ Nm}$

Schraubenanzugsmoment (5) M20x60 DIN EN ISO 4762-12.9, $T_A = 580 \text{ Nm}$
 screw tightening torque (6) M20x90 DIN EN ISO 4762-12.9, $T_A = 580 \text{ Nm}$

Oberflächengüte nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2		Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016			
Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768 - mH		Masstab Scale	1:5	Format DIN Size	A3
ROTEX 140 AFN-SB spez.				 KTR-Kupplungstechnik GmbH D-48407 Rheine	
gezeichnet drawn	Werkstoff Material	Teilnummer Part number	Kz	Lfd.-Nr. Current number	Index Change
Datum 27.02.12	DIN				
Name SCHP	Gewicht Weight	374.964	M	455229	1