


| Permissible misalignments<br>(max. figures may not occur simultaneously) |        |        | Coupling data             |            |
|--|--------|--------|---------------------------|------------|
| Angular (each lamina)  | Axial  | Radial | Nominal torque $T_{KN}$   | 200.000 Nm |
| 0.5°   | 4.5 mm | 3.0 mm | Maximum torque $T_{Kmax}$ | 400.000 Nm |

|  |          |                   |  |     |                    |        |                     |
|--|----------|-------------------|--|-----|--------------------|--------|---------------------|
| Oberflächengüte nach DIN ISO 1302 Reihe 2<br>Surface quality acc. to DIN ISO 1302 line 2   |          |                   | Schutzvermerk ISO 16016 beachten<br>Note protection mark acc. to ISO 16016   |     |                    |        |                     |
| Allgemeintoleranzen nach DIN ISO 2768 - mH<br>General tolerances acc. to DIN ISO 2768 - mH |          |                   | Masstab<br>Scale   | 1:5 | Format DIN<br>Size | A3     |                     |
| RADEX-N 288<br>NANA 1  |          |                   |  KTR-Kupplungstechnik<br>GmbH<br>D-48407 Rheine |     |                    |        |                     |
|  |          |                   |  |     |                    |        | gezeichnet<br>drawn |
| Datum  | 19.10.07 | DIN               |  |     | M                  | 465947 | 0                   |
| Name   | STA      | Gewicht<br>Weight | 512.610  |     |                    |        |                     |