


| Permissible misalignments (max. figures may not occur simultaneously) | | | Coupling data | |
|--|--------|---------|---------------------------|------------|
| Angular (each lamina) | Axial | Radial | Nominal torque T_{KN} | 70.000 Nm |
| 0,5° | 3,5 mm | 1,77 mm | Maximum torque T_{Kmax} | 140.000 Nm |

| | | | | | |
|--|-----------------------|-------------------|--|-----|----------------------------|
| Oberflächengüte nach DIN ISO 1302 Reihe 2 Surface quality acc. to DIN ISO 1302 line 2 | | | Schutzvermerk ISO 16016 beachten Note protection mark acc. to ISO 16016 | | |
| Allgemeintoleranzen nach DIN ISO 2768 - mH General tolerances acc. to DIN ISO 2768 - mH | | | Masstab Scale | 1:4 | Format DIN Size |
| | | | A3 | | |
| RIGIFLEX-N 258 A | | |  KTR-Kupplungstechnik GmbH D-48407 Rheine | | |
| gezeichnet drawn | Werkstoff Material | | Teilnummer Part number | Kz | Lfd.-Nr. Current number |
| Datum Date | 21.01.11 | DIN | | M | 466753 |
| Name | STA | Gewicht Weight | 382.679 | | Index Change |
| | | | | | 2 |