# IBExU Institut für Sicherheitstechnik GmbH

An-Institut der TU Bergakademie Freiberg

# [1] TYPE EXAMINATION CERTIFICATE - Translation

[2] for non-electrical products of equipment-groups I and II, equipment-categories M2 and 2 plus products of equipment-category 3



- [3] Type examination certificate number IBExU02ATEXB005 X | Issue 1
- [4] Product (equipment / component):

RADEX® - N Steel laminae couplings designs NN, NANA 1 to 5, NENA 1 and 2, NENE 1, NNZ, NNW, MK each in sizes up to 220 as well as with laminae packings with 4-hole-laminae or 6-hole-laminae

designs NN, NANA 1 to 4, NENA 1 and 2, NENE 1, NNZ, NNW in sizes 138, 158, 168, 208, 248, 288, 338 with laminae packings with 8-hole-laminae

[5] Manufacturer:

KTR Systems GmbH

[6] Address:

Carl-Zeiss-Straße 25

48432 Rheine GERMANY

- [7] This product and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- [8] IBEXU Institut für Sicherheitstechnik GmbH certifies that this product has been found to comply with the essential health and safety requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014.

The examination and test results are recorded in the confidential test report IB-18-2-0020.

- [9] Compliance with the essential health and safety requirements has been assured by compliance with: EN ISO 80079-36:2016 EN ISO 80079-37:2016 EN ISO/IEC 80079-38:2017 except in respect of those requirements listed at item [18] of the schedule.
- [10] If the sign "X" or "U" is placed after the certificate number, it indicates that the product is subject to the specific conditions of use specified in the schedule to this certificate.
- [11] This type examination certificate relates only to the design of the specified equipment and not to specific items of equipment subsequently manufactured or supplied.
- [12] The marking of the product shall include the following:

ⓐ || 2G | Ex h || C | T6 ... | T2 | Gb |
ⓑ || 2D | Ex h || C | T80°C ... | T250°C Db

-30°C ≤ Ta ≤ +60°C ... +230°C

IBExU Institut für Sicherheitstechnik GmbH Fuchsmühlenweg 7 09599 Freiberg, GERMANY

By order/

Dipl-Ing. Willamowski

IBEXU
Institut für Sicherheitstechnik GmbH
Fuchsmühlenweg 7
09599 Frei Stan 5 ach sen
Telefon (03731) 3805-0
Telefax (03731) 38 05 10

Tel: +49 (0) 37 31 / 38 05 0 Fax: +49 (0) 37 31 / 38 05 10

Certificates without signature and stamp are not valid. Certificates may only be duplicated completely and unchanged. In case of dispute, the German text shall prevail.

Freiberg, 2020-03-18

Page 1/3 IBExU02ATEXB005 X | 1

FB106109 | 1

# IBExU Institut für Sicherheitstechnik GmbH

An-Institut der TU Bergakademie Freiberg

[13] Schedule

## [14] Certificate number IBExU02ATEXB005 X | Issue 1

### [15] Description of product

The RADEX® - N Steel laminae couplings mentioned in [4] are backlash-free and torsionally-stiff couplings. The laminae packing made of stainless spring steel is clamped between two flanges so that axial, radial and angular displacements between input and output can be compensated within specified limits. The various types of couplings differ in particular in the number of joints (single-cardanic or double-cardanic), the design of the laminae (4-hole, 6-hole or 8-hole laminae) as well as in the arrangement of different spacers.

The laminae packings are screwed together either with fitting bolts and nuts or with fitting bolts and KTR clamping nuts.

Details on the design of the equipment or components can be found in the manufacturer's documentation and the test reports IB-02-4-124/2, IB-02-4-602, IB-02-4-602/1, IB-04-4-005, IB-04-4-016/2, IB-06-4-008, IB-08-4-019 und IB-18-2-0020.

Variations compared to issue 0 of this certificate:

#### Variation 1

Name and address of the manufacturer have changed.

#### Variation 2

The couplings were checked for compliance with the requirements of current standards.

#### [16] Test report

The test results are recorded in the confidential test report IB-18-2-0020 of 12.03.2020.

The test documents are part of the test report and they are listed there.

#### Summary of the test results

The equipment or components mentioned in [4] meets the requirements of explosion protection for equipment of Equipment Group II, Categories 2D or 2G or M2 in type of protection "c" (constructional safety, marking with "Ex h") for use with explosive dust and gas atmospheres and for underground use.

### [17] Specific conditions of use

- 1. The temperature marking indicates that for determining the maximum surface temperature occurring on the coupling a temperature increase  $\Delta T$  to the ambient or operating temperature  $T_a$  must be considered. The temperature increase  $\Delta T$  is stated in the operating instructions.
- 2. The RADEX® N Steel laminae couplings may only be used, if their materials resist, under the respective operating conditions, the mechanical and/or chemical effects and corrosion, so that the explosion protection is always maintained.
- 3. The users must provide the RADEX® N Steel laminae couplings with fixed covers in order to protect the couplings against falling objects. The covers can have openings for the necessary heat dissipation. When used in the mining industry (Equipment Group I), the covers of the couplings must be able to withstand higher mechanical loads than for use in other industries (Equipment Group II). Detailed information on the cover design is given in the operating / assembly instructions.

The covers must be electrically conductive and included in the equipotential bonding.

4. When using the couplings in potentially explosive dust atmospheres, the users must make sure that no dust in dangerous quantities accumulates between cover and coupling. The coupling must not run in a dust accumulation.

Page 2/3

# IBExU Institut für Sicherheitstechnik GmbH

# An-Institut der TU Bergakademie Freiberg

- 5. Only screws specified by the manufacturer may be used for the screw connections. When tightening the screws, the torque specified by the manufacturer must be observed.
- 6. All screw connections for mounting the hub onto the shafts must be secured against self-loosening.
- 7. For use of the couplings in the mining industry, the requirements of the national mining regulations valid for the respective area of application must be observed.

#### [18] Essential health and safety requirements

In addition to the essential health and safety requirements (EHSRs) covered by the standards listed at item [9], the following are considered relevant to this product, and conformity is demonstrated in the test report:

Clause

Subject

[19] Drawings and Documents

Number

Sheet

Issue

Date

Description

The documents are listed in the test report.

IBExU Institut für Sicherheitstechnik GmbH Fuchsmühlenweg 7 09599 Freiberg, GERMANY

By order

Dipl.-Ing. Willamowski

Freiberg, 2020-03-18